

Package: solidauthr (via r-universe)

June 7, 2026

Type Package

Title Solid OIDC Client Credentials Authentication

Version 0.1.2

Description Authenticates against Community Solid Server identity providers using OAuth client credentials with DPoP proofs and performs authenticated requests against Solid resources.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.1.0)

Imports htr2, jose, jsonlite, openssl, R6, uuid

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

URL <https://github.com/SetMeld/solidauthr>

BugReports <https://github.com/SetMeld/solidauthr/issues>

Config/pak/sysreqs libssl-dev

Repository <https://setmeld.r-universe.dev>

Date/Publication 2026-05-04 17:35:26 UTC

RemoteUrl <https://github.com/setmeld/solidauthr>

RemoteRef HEAD

RemoteSha 2b64749d5eda39f0438e13a1d22ce2afad3db492

Contents

solidauthr-package	2
solid_session	2

Index	4
--------------	----------

solidauthr-package	<i>solidauthr: Solid OIDC Client Credentials Authentication</i>
--------------------	---

Description

Utilities for authenticating against Community Solid Server identity providers with OAuth client credentials and DPoP, then issuing authenticated requests to Solid resources.

solid_session	<i>Create a Solid OIDC session</i>
---------------	------------------------------------

Description

Discovers the issuer's OpenID configuration, creates a session-scoped DPoP key, obtains DPoP-bound access tokens with the webid scope, and attaches fresh DPoP proofs to outgoing Solid requests.

Usage

```
solid_session(issuer, client_id, client_secret, safety_margin = 30L)
```

Arguments

issuer	A length-1 character vector giving the issuer base URL for a Community Solid Server identity provider.
client_id	A length-1 character vector giving the OAuth client ID.
client_secret	A length-1 character vector giving the OAuth client secret.
safety_margin	A number of seconds to subtract from token expiry when deciding whether a token should be refreshed.

Value

An R6 SolidSession object with methods for authenticated HTTP requests and access-token retrieval.

Examples

```
issuer <- Sys.getenv("SOLID_ISSUER")
client_id <- Sys.getenv("SOLID_CLIENT_ID")
client_secret <- Sys.getenv("SOLID_CLIENT_SECRET")

if (nzchar(issuer) && nzchar(client_id) && nzchar(client_secret)) {
  session <- solid_session(
    issuer = issuer,
    client_id = client_id,
```

```
    client_secret = client_secret
  )
  session$token()
}
```

Index

`solid_session`, [2](#)
`solidauthr (solidauthr-package)`, [2](#)
`solidauthr-package`, [2](#)